

HiPrene MT63I

HiPrene MT63I is a high-mod flow, 30% mineral filled polypropylene compound. The grade has very good impact/toughness balance. The grade is primarily designed for the Automotive Parts. Certified but it's suitable for other minor parts where it's necessary to have high impact resistance. This grade is specific for its low color and emission values.

	Properties	Test condition	Method	Unit	Value
Physical	Melt Mass-Flow Rate		ISO 1133-2/A	g/10min	16
	Specific Gravity		ISO 1183	g/cm ³	1,04
Mechanical	Tensile Strength	23° C	ISO 527-2/1A/50	MPa	18
	Nominal Tensile S-train at Break	23° C	ISO 527-2/1A/50	%	50
	Flexural Strength		ISO 178/B	MPa	20
	Flexural Modulus	23°C	ISO 178/B	MPa	1700
Impact	Notched Izod Impact Strength	23°C	ISO 180/A	KJ/m ²	35
Thermal	Volatile Matters		GS Standard SOP003	%	max. 0,15
	Ash Content	600°C	ISO 3451-1/A600°C	%	20

All values are approximate values and are given after the best knowledge and conscience. Hence, because of variable processing terms or processing procedures an obligation cannot be derived from it.

Tekuma Kunststoff GmbH is not the manufacturer of a.m. product. The information return the result of the quality inspection. An assurance of certain properties and qualities for specify uses cannot be derived. We recommend additional tests with regard to the suitability ability. Guarantee occurs within the scope of our general terms of sale and terms of delivery.